



Regulation No. 305/2011 DOP-Scan-Line 805 Aqua-1757-2013

1. Model identifier	Scan-Line 800 Aqua, 805 Aqua
Intended use or uses of the construction product, in accordance with the applicable technical specification	Room heater solid fuel, space heating in residential building
3. Name and contact address of the manufacturer	Heta A/S, Jupitervej 22, DK-7620 Lemvig. heta@heta.dk
System of assessment and verification of constancy of performance of the construction product	System 3
Notified body relevant to the assessment and verification of constancy of performance	Danish Technological Institute, DK-8000 Aarhus Notified body No. 1235. Report nr. 300-ELAB-1757-EN

6. Essential characteristics

Mechanical resistance and stability	20 kg Load bearing capacity			
Fire safety				
Minimum distance to combustible materials	Minimum distances in mm			
Bottom (dB) Ceiling (dC) Rear (dR) Side (dS) Furniture in front (dP) Corner (45°) (dS!) Floor front (dF) Side radiation area (dL) Ceiling/ Mantel (dC!) Door to hearth (dB!)	0 (<65K) 750 20 225 750 20 0 (<65K) 0 (<65K) NPD 153			
Hygiene, health and the environment				
Emissions at nominal heat output (Harmonized technical specification EN 16510-2-1-2022)				
CO (≤) 1500 mg/m³ 666 mg/Nm³ Nox (≤) 200 mg/m³ 115 mg/Nm³ OGC (≤) 120 mg/m³ 56 mgC/Nm³ at 13% O₂ Particles (≤) 40 mg/m³ 22 mg/Nm³				

Safety and accessibility in use

Data for installation to a chimney at nominal heat output			
Flue gas outlet temperature	224 °C		
Minimum flue draught	12 Pa		
Flue gas mass flow	6,6 g/s		
Data for installation to a chimney regarding fire safety test heat output			
Fire safety of installation to the chimney	T400G		

Energy economy and heat retention

Appliance's thermal output and energy efficiency at nominal heat output			
Space heat output		8,7 kW	
Room heat output		3,1 kW	
Water heating output		5,6 kW	
Maximum water operating pressure		4 Bar	
Efficiency	≥ 75%	<i>η</i> 87%	
Seasonal space heating efficiency at appliance's nominal heat output	≥ 65%	η _s 77%	
Energy efficiency		116	
		A+	

7.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf the manufacturer of 31.10.2025